

GOODWE Limited Warranty for LX D G2 Battery System **(for EU Market)**

OVERVIEW

GoodWe Technologies Co., Ltd (hereinafter referred to as GOODWE) warrants that, subject to the exclusions and limitations set out below, the GOODWE LX D G2 Series battery system GW5.1-BAT-D-G20, GW8.3-BAT-D-G20, GW6.0-BAT-D-G20 and GW9.0-BAT-D-G20 come with a *Manufacturer's warranty which includes

1. Limited product warranty: GOODWE warrants that the hardware of electronics and enclosure (including battery cover, micro circuit breaker, BMS PCBA) will be free of defects caused by improper workmanship or defective materials and it will be starting from the original end user purchase date, if the customer is unable to provide adequate documentation of the original purchase, the warranty starting date shall be the earlier one of installation date or 6 months after the product was manufactured.
2. Limited performance warranty: GOODWE warrants that,
 - a. for ten (10) years , the battery system (i) retains either seventy percent (70%) of *Usable Energy from the warranty period from the dispatch from GOODWE; or (ii) reach the *Minimum Through Output Energy, whichever comes first.
 - b. for fifteen (15) years, the battery system (i) retains either sixty percent (60%) of *Usable Energy from the warranty period from the dispatch from GOODWE; or (ii) reach the *Minimum Through Output Energy, whichever comes first.
3. See the table below for details

Product models	Usable Energy	Standard warranty period	Minimum Throughput DC Energy per kWh Usable Battery Capacity	Extended warranty	Minimum Throughput DC Energy per kWh Usable Battery Capacity
GW5.1-BAT-D-G20	5.0 kWh	10 years	3.00 MWh	NA	NA
GW8.3-BAT-D-G20	8.0 kWh				
GW6.0-BAT-D-G20	5.8 kWh	10 years	3.51 MWh	+5 years	4.22 MWh
GW9.0-BAT-D-G20	8.7 kWh				

PRECONDITIONS FOR WARRANTY

1. The defect of the battery system shall occur within the battery system warranty period as determined above.
2. Any battery system failure, fault or warning which leads to system not working or working abnormally, must be reported by following the terms described in 'HOW TO MAKE A CLAIM UNDER THE GOODWE LIMITED WARRANTY' within two weeks of appearance.
3. The battery system shall only be installed by a professional installers who are qualified according to local regulations.
4. End User shall correctly operate and use the battery system according to the User Manual and Installation Guide.
5. End User shall provide the proof of the original purchase of the battery system.
6. The installation of the Battery system for the End User shall be completed within maximum 6 months from the production date. If the equipment is not to be installed or used immediately, please ensure that the storage environment meets the following requirements:
 - a) Do not unpack the outer packing box or throw the desiccant away.
 - b) Complete the equipment installation in three days after unpacking it. Pack and store the equipment using the original packing box if it is not installed.
 - c) Stack the equipment complying with the labels and requirements on the packing box.
 - d) The equipment must be stacked with caution to prevent them from falling.
 - e) Keep the equipment away from flammable, explosive, and corrosive matters.
 - f) Place the equipment in a cool place where away from direct sunlight.
 - g) Store the equipment in a clean place. Make sure the temperature and humidity are appropriate and no condensation.
 - h) Recommended storage temperature for GW5.1-BAT-D-G20 and GW8.3-BAT-D-G20: 0~35℃; -18℃~35℃circle the charge/discharge every 12 months; 35℃~45℃circle the charge-discharge every 6 months.
 - i) Recommended storage temperature for GW6.0-BAT-D-G20 and GW9.0-BAT-D-G20: 0~35℃; -20℃~35℃circle the charge/discharge every 12 months; 35℃~45℃circle the charge-discharge every 6 months; 45℃~55℃circle the charge-discharge every month.
 - j) Recommended storage humidity: 5%~95%RH (no condensation). Do not install the battery if there is any moisture or condensation.

7. If the Battery system is stored for a long time, the irreversible capacity loss may occur. The storage capacity of the battery may not meet 100% of the rated capacity, if customers perform the discharge test according to the specifications after long storage.
8. The charging/ discharging temperature of the battery system must NOT exceed -18℃~55℃ and shall not be exposed in an installed area to direct sunlight. The Battery system installation location must be ventilated in accordance with the requirements of User Manual and Installation Guide.
9. This Warranty covers a capacity equivalent to one full cycle per day. The Battery system is not suitable for supplying life-sustaining medical devices or automotive application.
10. Support capacity expansion, unlimited production time. The total capacity is accumulated based on the actual capacity.
11. When expanding/maintaining, please cooperate with the inverter to carry out a full charge and discharge cycle.

HOW TO MAKE A CLAIM UNDER THE GOODWE LIMITED WARRANTY

If the claimant wants to make a warranty claim, please contact your local distributor where you purchased the battery system from, or the installer who installed the inverter for you. If the claimant was unable to obtain service from them, or was NOT satisfied with their service, the claimant can escalate your service request by creating a service ticket and make a claim to GOODWE via <https://goodwetechnology.zendesk.com/hc/en-gb>. Please note, in order to deliver a friendly and timely service, GOODWE is cooperating with many of our distributors and installers all over the world. As such, please treat them as the default service channel of GOODWE and use these service channels to make your warranty claim; GOODWE will support and audit our service channel to ensure that we deliver a good service to our customers.

Please have the following information to hand as it may be required when contacting the local distributor.

1. Contact information of claimant, including name of the person, name of the company, phone number, email address and shipment address.
2. Information regarding all defective battery system, including model No., serial number, installation date and failure date. Please make the claim within one month from the failure date, otherwise GOODWE will treat it as you have abandoned the right to make a warranty claim.
3. Installation information, including brand, model, and number of PV panels.
4. Error message on APP screen (if applicable) and additional information regarding the fault/error.
5. Description of actions before the failure and detailed information of previous claims (if applicable).

GOODWE may arrange an on-site inspection to find out the root of the faults. The claimant is responsible for granting access, making time, and ensuring the safety of the inspection by a technician from GOODWE or an authorized third-party company. GOODWE reserves the right not to enter the site should the GOODWE technician consider it unsafe to do so.

REMEDY

If a claim is received within the warranty period and a fault with the battery system is discovered that is covered under the warranty, GOODWE may, at its sole discretion, either

1. fix the issue by changing configurations or updating software; or
2. repair the battery system by replacing with spare parts; or
3. replace the battery system for a battery system that is brand new or refurbished but at least functionally equivalent to the original battery system, or an upgraded model which is either functionally equivalent or functionally superior to the original battery system. If the device is replaced within the warranty period, the remaining warranty period will be automatically transferred to the replacement unit. If the remaining warranty period is less than half a year after the replacement, it will be extended to a 6 months warranty. For every single battery system replacement case, the claimant must gather the necessary information and send the RMA report (by following GOODWE's RMA template) to GOODWE to confirm the RMA request, prior to the battery system being replaced.

All parts of the battery system that GOODWE replaces shall become GOODWE's property. If the battery system is found not to be covered by this Limited Warranty, GOODWE reserves the right to charge a handling fee.

WHAT IS COVERED AND NOT COVERED?

Unless a special/unique agreement exists between GOODWE and the customer, the GOODWE limited warranty covers only the cost of hardware material required to get the device functioning again.

Transportation costs: in some areas, GOODWE will cover the outbound and inbound transportation costs by using normal ground transportation up to a total amount (please contact GOODWE for the rate). The claimant must cover any excess costs or any costs generated by using another method of transportation. In some of the cases, the claimant need to organize the return of the allegedly defective battery system to GOODWE and should confirm with GOODWE for the shipment schedule in advance. As battery systems need to be packaged in a reasonable condition, GOODWE suggests using packaging material that is the same size as the battery system package at the time of purchase. If the allegedly defective battery system is not returned within 4 weeks of the

replacement unit being received by the claimant, or there's no damage found after checking the returned back battery system, GOODWE will invoice the claimant for the replacement unit in addition to the delivery and associated service charges.

On-site service labor costs: in some areas or business cases, to encourage the claimant using the installer's facilities to fix the problem, GOODWE may, at its sole discretion, decide to offer a rebate (please contact GOODWE for the rate) to the claimant or local installer/electrician to cover the on-site service labor under the following conditions:

1. The rebate will be eligible ONLY to the party who has carried out on-site service for the allegedly defective battery system.
2. The allegedly defective battery system has been returned to GOODWE and deemed to have workmanship or material defects upon testing and inspection by GOODWE.
3. The claimant must contact GOODWE prior to the site visit for authorization. If the site is a remote area or if the installer is unable to be on site, GOODWE recommends the claimant find a local electrician to carry out the on-site service.
4. The service rebate must be claimed within 2 months of the date upon which the on-site service is authorized by GOODWE.
5. The total labor cost (including TAX/GST) shall NOT exceed a total amount (please contact GOODWE for the rate) per case.

All other costs including but not limited to compensation from direct or indirect damages arising from the defective device or other facilities of the PV system, or loss of electrical power generated during the battery system downtime are NOT covered by the GOODWE limited warranty.

WARRANTY EXCEPTIONS

The following circumstances may cause device defects, but are NOT covered by GOODWE's limited warranty.

1. Normal wear and tear.
2. Any defects that occur when the battery system warranty period has expired (excluding additional agreements of warranty extension).
3. Product installation MUST be performed by trained installers. If it's proven that the problem was caused by faulty installation, the faults or damages are NOT covered by GOODWE's limited warranty.
4. Failure or damages due to failure to observe the product manuals or related installation and maintenance requirements.
5. Faults or damages due to faulty installations or operations, maintenance carried out against GOODWE instructions by an unauthorized installer.
6. Damage caused by End User deliberately or by willful act.
7. Disassembly, repair or modifications performed by a third-party company/person not authorized by GOODWE. Battery system modifications, design changes or part replacements not approved by GOODWE.
8. Faults or damages due to unforeseen circumstances, man-made factors, or examples of force majeure including but not limited to stormy weather, flooding, overvoltage, pests, inappropriate handling, misuse, neglect, fire, water, lightning or other acts of nature.
9. Vandalism, engraving, labels, irreversible marking or contamination or theft.
10. Faults or damage caused by other factors not related to battery system quality issues.
11. Any rust that appears on the device's enclosure caused by harsh environmental conditions, accidents and external influences. Faults or damage caused by exposure to sea coasts/saltwater or other aggressive atmospheres or environmental conditions without GOODWE's written confirmation/approval prior to the installation.
12. Damage caused during transport, incorrect product installation, removal, exceedance of temperature range during use and improper use.
13. End User fails to provide correct product serial number or product serial number is undecipherable or has been modified without permission by GOODWE.
14. Defects of Product arise due to renewal of the national or regional laws or regulations.
15. Product failure is not reported to GOODWE within two weeks of appearance.

OUT-OF WARRANTY-CASE

Any defects that occur after the expiry of the warranty period, or which occur within the warranty period but which falls into the warranty exceptions conditions above, are known by GOODWE as out-of-warranty cases. For all out-of-warranty cases, GOODWE may charge an on-site service fee, a parts fee, labor costs and a logistics fee to customer, including any/all of:

1. On-site service fee: cost of travel and time for the technician to deliver on-site service and labor cost for the technician, who is repairing, performing maintenance on, installing (hardware or software) and debugging the faulty battery system.
2. Parts/materials fee: cost of replacement parts/materials (including any shipping/admin fee that may apply).
3. Logistics fee: cost of delivery and any other expenses incurred when defective battery systems are sent from the user to GOODWE or/and repaired battery systems are sent from GOODWE to the user.

GEOGRAPHICAL SCOPE

The GOODWE Limited warranty terms and conditions only apply for the devices which are originally purchased from channels authorized by GOODWE and installed in Europe market, unless there are specially stipulated warranty terms and conditions between GOODWE and the direct purchaser. For any units sold for installation in one country/region but installed in another country/region, the warranty will become invalid if GOODWE does not provide written confirmation/approval prior to the installation.

LIMITATION OF GOODWE's LIABILITY

This limited warranty applies to the battery system which is sold and installed after October, 2024. It is the end user's sole and exclusive remedy against GOODWE and GOODWE's sole and exclusive liability in respect of defects in battery system. This limited warranty replaces all other GOODWE warranties and liabilities, whether oral, written, (non-mandatory) statutory, contractual, in tort or otherwise, including, without limitation, and where permitted by applicable law, any implied conditions, warranties or other terms as regards satisfactory quality or fitness for purpose. However, this limited warranty shall neither exclude nor limit any of your legal (statutory) rights under the applicable national laws. To the extent permitted by applicable law(s), GOODWE does not assume any liability for any loss of, damage to or corruption of data, for any loss of profit, loss of use of battery systems or functionality, loss of business, loss of contracts, loss of revenue or loss of anticipated savings, increased costs or expenses or for any indirect loss or damage, consequential loss or damage or special loss or damage, or punitive loss or damage. To the extent permitted by applicable law, GOODWE's liability shall be limited to the purchase value of the battery system. The above limitations shall not apply in case of gross negligence or intentional misconduct of GOODWE or in case of death or personal injury resulting from GOODWE's proven negligence.

*Manufacturer's warranty is a basic warranty promise from GOODWE to the end users. In some countries/districts, end users may receive an additional warranty promise (should be at least equivalent to the manufacturer's warranty) which is provided by GOODWE's local distributor; should any claims arise in this respect, please direct them to the local distributor. Please note this GOODWE limited warranty statement may NOT be the latest version, please refer to the latest version of the GOODWE limited warranty by visiting our global website via <https://en.goodwe.com/warranty.asp>

*The Minimum Through Output Energy estimate simulation conditions

- 1) for GW5.1-BAT-D-G20 and GW8.3-BAT-D-G20: ambient temperature 10~25°C, on average ≤ one cycle a day, and the maximum charge/discharge current ≤50A.
- 2) for GW6.0-BAT-D-G20 and GW9.0-BAT-D-G20: ambient temperature 10~30°C, on average ≤ one cycle a day, and the maximum charge and discharge current follows the battery system charge and discharge map.

*Usable Energy (KWh) needs to be measured by following the testing conditions and methods in Appendix A

Appendix A

1. Capacity measurement condition: Ambient temperature: 25±2°C, and testing should be conducted after at least 12 hours of storage.
2. Charge / Discharge method for GW5.1-BAT-D-G20 and GW8.3-BAT-D-G20 :
 - 1) Discharge the battery with 0.2P constant current until any cell reaches the cut-off voltage.
 - 2) Lay aside the battery for 30mins.
 - 3) Charge the battery with 0.2P constant current until any cell reaches the cut-off voltage.
 - 4) Lay aside the battery for 30mins.
 - 5) Discharge the battery with 0.2P constant current until any cell reaches the cut-off voltage.
 - 6) Repeat steps 2) to 5) three times, take the discharge capacity of the third cycle as the final capacity.
3. Charge / Discharge method for GW6.0-BAT-D-G20 and GW9.0-BAT-D-G20:
 - 1) Discharge the battery with 0.4P constant current until any cell reaches the cut-off voltage.
 - 2) Lay aside the battery for 30mins.
 - 3) Charge the battery with 0.4P constant current until any cell reaches the cut-off voltage.
 - 4) Lay aside the battery for 30mins.
 - 5) Discharge the battery with 0.4P constant current until any cell reaches the cut-off voltage.
 - 6) Repeat steps 2) to 5) three times, take the discharge capacity of the third cycle as the final capacity.